

# **DARPA Phoenix Payload Orbital Delivery (POD) System: Progress towards Small Satellite Access to GEO**

---

Erin Fowler – DARPA SETA

Coauthors:

LtCol Larry Gunn, Dr. Jeremy Palmer – DARPA Program Managers

Joanne Leung, Andrew Ogilvie – MDA Robotics and Automation

Al Tadros, Laurie Chappell – Space Systems/Loral

Ken Weldy – Naval Research Laboratory

Jim Eagen, Dr. Brook Sullivan – DARPA SETAs

Briefing prepared for Small Satellite Conference 2015

August 10, 2015




The views, opinions and/or findings contained in this article/presentation are those of the authors and should not be interpreted as representing the official views or policies, either expressed or implied, of the Defense Advanced Research Projects Agency or the Department of Defense.

Distribution Statement A. Approved for public release; distribution is unlimited.




## Payload Orbital Delivery (POD) System Summary

- **Releasable** hosted payload
- Delivers up to **90 kg** (standard) or **150 kg** (extended) to orbit
- Launch opportunities to **GEO and GTO** multiple times per year





## SSL Satellite Locations Frequently Available for POD Rideshare



© SSL

Unused Battery Compartments on East/West Faces

Mid-Panel on East/West Faces




© SSL



## Annual POD Hosting Opportunities (FAA 2014 Commercial Space Transportation Forecast)

- ~15 launches per year through 2023
- ~5-7 could be able to accommodate a POD







## Typical POD Launch Mission Timeline, Mass and Volume Options


Event	Milestone Date
Contract Signing	Launch – 24 months
Separation System Delivery	Launch – 12 months
POD or POD mass model delivery	Launch – 9 months
PODS Final Integration to Host	Launch – 2 months
Ship to Launch Base	Launch – 1 month
Launch	Launch

HPA Option	HPA Maximum Mass	HPA Volume [L x W x H]
Standard HPA	90 kg	90.9 x 45.7 x 40.0 cm <sup>3</sup>
Extended HPA	150 kg	90.9 x 90.9 x 60.0 cm <sup>3</sup>

Payload Mass Range	Payload Footprint
15 Kg – 30 Kg	20 cm x 20 cm (minimum)
30 Kg – 60 Kg	30 cm x 30 cm (minimum)



## Standard Hosted POD Assembly (HPA)




© MDA

Patent Pending (PCT/CA2015/050451)



## Standard POD Chassis (Underside) to POD Ejection Mechanism (PEM) Interfaces




Interfaces between the POD chassis and POD Ejection Mechanism (PEM):

- Launch lock brackets
- Final central tie-down
- Ejection contact points




# Hosted POD Assembly (HPA) Ground Test Results

Successful green runs before June 2015 HPA CDR



Engineering Models on HPA  
Performance Test Rig at MDA Robotics  
and Automation

© MDA



Fastener Release Test for POD Final  
Tiedown (Universal Docking System [UDS]  
from MDA US LLC) – Severed Fastener

© MDA





## Future of POD

---

- **The first deployment of a POD in orbit is planned for March 2017.**
- The POD system could enable **high delivery tempo to GEO for small payloads.**
- Once the POD system capability is established, a POD could be **integrated into a host spacecraft quite late in the integration flow**, creating an “express delivery to GEO” capability.
- Designing and verifying the POD system to a standard user’s guide could ensure **compatibility with most of the ~15 commercial launches to GEO each year.**
- Other satellite providers besides SSL should be able to accommodate PODs with limited development and impact to existing bus designs as a new method for **delivering small-mass hardware items, small spacecraft and potentially fuel** to GEO at a higher tempo than has previously been possible.
- **New concepts of operation** could be considered:
  - A host satellite could conceivably take advantage of on-orbit robotic services to have a new electronics box attached via the empty POD mechanical, power and data connections where the POD was ejected.
  - This concept raises the entirely novel possibility of adding new capabilities, providing external diagnostics or adding fresh revenue streams to existing on-orbit spacecraft.



## For more information

---

- On SSL POD flight opportunities:
  - Al Tadros, SSL (al.tadros@sslmda.com, (650) 714-0439)
  - Laurie Chappell, SSL (laurie.chappell@sslmda.com, (650) 852-2569)
- On DARPA Phoenix program:
  - Dr. Jeremy Palmer, DARPA PM (jeremy.palmer@darpa.mil)



[www.darpa.mil](http://www.darpa.mil)